

Information and complexity

Channel coding

Dimitri Petritis

Institut de recherche mathématique de Rennes
Université de Rennes 1 et CNRS (UMR 6625)

September 2022

Channels

Markovian modelling

- **Channel** = general notion. Initially meant to study transmission of a coded message through noisy medium.
- Presently, to mean arbitrary transformation of a word of a finite alphabet to another word of a (may be different) finite alphabet.
- **Input:** random word $\mathbf{X} \in \mathbb{X}^+$, where \mathbb{X} input alphabet.
- **Output:** random word $\mathbf{Y} \in \mathbb{Y}^+$, where \mathbb{Y} output alphabet..
- **Transmission probability:** conditional probability $\mathbb{P}(\mathbf{Y} = \mathbf{y} | \mathbf{X} = \mathbf{x})$.
- Assume (for simplicity)
 - input and output words of same length; i.e. $|\mathbf{x}| = |\mathbf{y}|$ and
 - input symbols emitted by independent source.

Both hypotheses can be relaxed at the price of more complicated formulæ.

Channels

Ideal and realistic

- Transmit 1 bit of information = transport the precise state — of physical system encoding the bit — through a physical medium or process — the channel:

Transmission vector	Ideal channel	Realistic channel
electric current	ideal copper wire	copper wire with > 0 resistivity
Hertzian beam	empty space	atmosphere
laser beam	empty space or fiber	fiber not 100% transparent
photon	empty space or fiber	fiber not 100% transparent
DNA	cellular mitosis/meiosis	mutations
...

- \Rightarrow transmission errors.

Channels

Markovian modelling (cont'd)

Definition

$(p_n)_{n \in \mathbb{N}}$, $n \in \mathbb{N}$, sequence defined by

$$\mathbb{X}^n \times \mathbb{Y}^n \ni (\mathbf{x}, \mathbf{y}) \rightarrow p_n(\mathbf{x}, \mathbf{y}) := \mathbb{P}(\mathbf{Y} = \mathbf{y} | \mathbf{x} = \mathbf{x}) \in [0, 1].$$

- Triple $(\mathbb{X}, \mathbb{Y}, (p_n)_{n \in \mathbb{N}})$ **discrete channel**.
- Channel is **memoryless** if exists stochastic matrix $P : \mathbb{X} \times \mathbb{Y} \rightarrow [0, 1]$ s.t. for all $n \in \mathbb{N}$, $\mathbf{x} \in \mathbb{X}^n$, and $\mathbf{y} \in \mathbb{Y}^n$, conditional probability reads $p_n(\mathbf{x}, \mathbf{y}) = \prod_{i=1}^n P(x_i, y_i)$.

Memoryless channel identified with triple $(\mathbb{X}, \mathbb{Y}, P)$, where P a $|\mathbb{X}| \times |\mathbb{Y}|$ -stochastic matrix.

3-A: Examples and illustration of the generality of the notion of channel.

ex 1: $X = Y = \{0,1\}$ $P = \begin{matrix} 0 & 1 \\ 1 & 0 \end{matrix} \begin{bmatrix} 1-p_0 & e_1 \\ e_0 & 1-p_1 \end{bmatrix}$ $e_0, e_1 \in [0,1]$
 $|X| = |Y| = 2$

$\mathbb{P}(Y=110 | X=010) = P(0,1)P(1,1)P(0,0) = e_1(1-e_1)(1-p_0)$

ex: $X = \{a, b, c, d\}$ $A = \{0,1\}$ $C: X \rightarrow A^+$

x	$C(x)$
a	0
b	10
c	110
d	111

instantaneous code can be viewed as

(X, Y, P) channel $Y = C(X) = \{0, 10, 110, 111\}$

$P = \begin{matrix} a \\ b \\ c \\ d \end{matrix} \begin{bmatrix} 0 & 10 & 110 & 111 \\ 1 & 1 & 1 & 1 \end{bmatrix}$

Sources and channels

Reminder

If source law is $\mu \in \text{PV}_{\mathbb{X}}$ and channel transmission matrix is P , can compute

- source entropy $H(X) \leftarrow -\sum \mu(x) \log \mu(x)$
- joint law of input-output $\kappa(x, y) = \mathbb{P}(X = x, Y = y) = \mu(x)P(x, y)$
(hence joint entropy $H(X, Y) \leftarrow -\sum_{x,y} \kappa(x,y) \log \kappa(x,y) = -(\mu P) \log(\mu P)$)
- output law $\nu(y) = \sum_{x \in \mathbb{X}} \kappa(x, y) = \sum_{x \in \mathbb{X}} \mu(x)P(x, y)$ (hence output entropy $H(Y)$),
- conditional entropies $H(X|Y)$ and $H(Y|X)$ and mutual information $I(X : Y)$.

 $H(X, Y)$
 $H(X)$
 $H(Y)$
 $H(X|Y)$
 $I(X : Y)$
 $H(Y|X)$

Channels

Channel classification

Channels without loss: characterised by $H(X|Y) = 0$; if output is known, no residual uncertainty on input. Equivalently
 $I(X : Y) = H(X) - H(X|Y) = H(X)$.

Deterministic channels: their transmission matrix is deterministic i.e.

$$\forall x \in \mathbb{X}, \exists! y := y_x \in \mathbb{Y}, P(x, y_x) = 1.$$

If μ source law,

$$\mathbb{X} \times \mathbb{Y} \ni (x, y) \mapsto \kappa(x, y) = \mu(x)P(x, y) = \mu(x)\delta_{y_x, y}.$$

Hence $H(X, Y) = H(\kappa) = H(X)$, $H(Y|X) = H(X, Y) - H(X) = 0$
 and $I(X : Y) = H(Y) - H(Y|X) = H(Y)$, i.e. if input is known, no residual uncertainty on output.

Noiseless channels: without loss ($H(X|Y) = 0$) and deterministic ($H(Y|X) = 0$).
 Hence $I(X : Y) = H(X) = H(Y)$.

Useless channels: $\forall \mu \in \text{PV}_{\mathbb{X}}, I(X : Y) = 0$. Hence

$$0 = I(X : Y) = H(X) - H(X|Y) = 0 \Rightarrow H(X) = H(X|Y),$$

i.e. input, X , and output, Y , variables independent.

Symmetric channels: continues to next slide ...

Channels

Channel classification (cont'd)

Symmetric channels (cont'd): S_n permutation group on n objects and $(\mathbb{X}, \mathbb{Y}, P)$ memoryless channel. $|\mathbb{X}| = n$

Definition

Assume $\exists p \in PV_{\mathbb{Y}}$ and $\exists z \in [0, 1]^{|\mathbb{X}|}$, s.t.

- 1 $\forall x \in \mathbb{X}, \exists \sigma_x \in S_{|\mathbb{Y}|} : \forall y \in \mathbb{Y}, P(x, y) = p(\sigma_x y)$ and
- 2 $\forall y \in \mathbb{X}, \exists \sigma_y \in S_{|\mathbb{X}|} : \forall x \in \mathbb{X}, P(x, y) = z(\sigma_y x)$.

Then channel is **symmetric**.

3-B: Examples of various types of channels.

a) Lossless $H(X|Y)=0 \Rightarrow J(X;Y)=H(X)$

$$X = \{x_1, \dots, x_n\} \quad Y = \bigsqcup_{i=1}^m B_i \quad B_i \neq \emptyset$$

(P(n,m))

$$P(Y \in B_i | X = x_i) = \sum_{y \in B_i} P(x_i, y) = 1$$



⋮



$$P(X = x_i | Y \in B_i) = 1$$

Determinist.

52 cards = $X \times Y = X$ $X_1 = \{1, \dots, 10, J, Q, K\}$...
 $Y = Y_2 = \{\heartsuit, \diamondsuit, \clubsuit, \spadesuit\}$

$X \in X$

$Y \in Y$

$$I(X; Y) = \frac{H(Y) - H(Y|X)}{2} = \frac{H(Y)}{2}$$

noiseless lossless + det

a ————— a'

b ————— b'

$$I(X; Y) = H(X) = H(Y)$$

Symmetrie:

$$P_1 = \begin{bmatrix} 1/3 & 1/3 & 1/6 & 1/6 \\ 1/6 & 1/6 & 1/3 & 1/3 \end{bmatrix}$$

$$X = \{0,1\}$$

$$Y = \{a, b, c, d\}$$

$$P_2 = \begin{bmatrix} 1/2 & 1/3 & 1/6 \\ 1/6 & 1/2 & 1/3 \\ 1/3 & 1/6 & 1/2 \end{bmatrix} = P$$

$$I(X; Y) = H(Y) - H(Y|X) \\ = H(Y) - H(P)$$

Channel capacity

Definition

For fixed channel (i.e. fixed transmission matrix P), **capacity of the channel** is the quantity

$$\text{cap} := \text{cap}(P) = \sup_{\mu \in \mathcal{M}_1(\mathbb{X})} I(X : Y).$$

Remark

For the moment significance of capacity unclear. Two main results can be established:

- 1 if transmission rate $R < \text{cap}$, possible to transmit information with arbitrarily small error;
- 2 if $R > \text{cap}$, impossible to make transmission error vanish.



Channel capacity (cont'd)

Proposition

$(\mathbb{X}, \mathbb{Y}, P)$ noiseless channel with capacity cap .

- 1 $\text{cap} \geq 0$.
- 2 $\text{cap} \leq \log \text{card} \mathbb{X}$.
- 3 $\text{cap} \leq \log \text{card} \mathbb{Y}$.

Fix reasonable decoding rule $\Delta : \mathbb{Y} \rightarrow \mathbb{X}$ guessing .

Definition

Channel $(\mathbb{X}, \mathbb{Y}, P)$. The decision rule = guessing the emitted symbol $x \in \mathbb{X}$ when the received symbol is $y \in \mathbb{Y}$. The rule

$$\Delta(y) \in \arg \max_{z \in \mathbb{X}} \mathbb{P}(X = z | Y = y), y \in \mathbb{Y}$$

is called **of maximum likelihood** decision rule.

Channel capacity

Example

Example

Channel $(\mathbb{X}, \mathbb{Y}, P)$ with $\mathbb{X} = \{x_1, x_2, x_3\}$, $\mathbb{Y} = \{y_1, y_2, y_3\}$, and

$$P_{xy} := \mathbb{P}(Y = y | X = x) = \begin{pmatrix} 0.5 & 0.3 & 0.2 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.3 & 0.4 \end{pmatrix}.$$

3-C: Work out this example.

Definition

A **decision rule** is a stochastic kernel

$$K_{\Delta} : \mathbb{Y} \times \mathbb{X} \rightarrow [0, 1]$$

assigning to every received symbol $y \in \mathbb{Y}$ a probability $K_{\Delta}(y, x)$ for every possibly emitted symbol $x \in \mathbb{X}$.

$$\Delta(y) = \operatorname{argmax}_z$$

$$\mathbb{P}(X=z | Y=y)$$

$$P = \begin{bmatrix} 0.5 & 0.3 & 0.2 \\ 0.2 & 0.3 & 0.5 \\ 0.3 & 0.2 & 0.4 \end{bmatrix}$$

$$\begin{array}{ccc} \hline 1 & 0.9 & 1.1 \end{array}$$

Caution: $\neq P_{zy}, \neq P_{yz}$

$$\hat{P}_{yz} = \mathbb{P}(X=z | Y=y) = \frac{\mathbb{P}(X=z, Y=y)}{\mathbb{P}(Y=y)} = \frac{\mu(z) P_{zy}}{\sum_w \mu(w) P_{wy}}$$

Let $\mu = \text{unif}$

$$\hat{P}_{yz} = \frac{P_{zy}}{\sum_w P_{wy}} = (\hat{P}^U)_{zy}$$

$$\hat{P}^U = \begin{bmatrix} 0.5 & 0.333... & 0.1818... \\ 0.2 & 0.37... & 0.4545... \\ 0.3 & 0.33... & 0.3636... \end{bmatrix} \quad \hat{P} = \begin{bmatrix} 0.5 & 0.2 & 0.3 \\ 1/3 & 1/3 & 1/3 \\ 0.18 & 0.45 & 0.36 \end{bmatrix}$$

y	$\operatorname{argmax}_z \hat{P}_{zy}$
y_1	$\{z_1\}$
y_2	$\{z_1, z_2, z_3\}$

$$y_3 \mid \{z_2\}$$

$$x^* \in \operatorname{argmax}$$

$$\Delta(y) = x^*$$

Coding of a noisy channel

Want to transmit n -letter words over \mathbb{X} through memoryless channel $(\mathbb{X}, \mathbb{Y}, P)$.

Consider

- either channel $(\mathbb{X}, \mathbb{Y}, P)$ transmitting (sequentially, i.e. letter by letter) *random words* $\mathbf{X} = X_1 \cdots X_n \in \mathbb{X}^n$ towards *random words* $\mathbf{Y} = Y_1 \cdots Y_n \in \mathbb{Y}^n$ according to the transmission matrix P ,

$$\mathbb{P}(\mathbf{Y} = \mathbf{y} | \mathbf{X} = \mathbf{x}) = \prod_{i=1}^n P(x_i, y_i) =: Q_n(\mathbf{x}, \mathbf{y}),$$

$$Q = (q_1 \cdots q_n)$$


- or extended channel to $(\mathbb{X}^n, \mathbb{Y}^n, Q_n)$, where Q_n is the transmission matrix between \mathbb{X}^n and \mathbb{Y}^n transmitting (globally) *random words* $\mathbf{X} \in \mathbb{X}^n$ towards *random words* $\mathbf{Y} \in \mathbb{Y}^n$ according to the transmission matrix Q_n ,


$$\mathbb{P}(\mathbf{Y} = \mathbf{y} | \mathbf{X} = \mathbf{x}) =: Q_n(\mathbf{x}, \mathbf{y}),$$

Coding of a noisy channel (cont'd)

Actions considered separately


- Sets of words \mathbb{X}^n and \mathbb{Y}^n not of direct interest.
- Set of messages \mathbb{M} encoded into words of \mathbb{X}^n and words of \mathbb{Y}^n decoded into messages of \mathbb{M} .
- Two mappings
 - coding $\mathbb{M} \ni m \mapsto \mathbf{C}(m) \in \mathbb{X}^n$ and
 - decoding (deterministic or random) rule $\mathbb{Y}^n \ni \mathbf{y} \mapsto \Delta(\mathbf{y}) \in \mathbb{M}$.


 $m \mapsto \mathbf{C}(m)$

 $y \mapsto \Delta(\mathbf{y})$


Coding of a noisy channel (cont'd)

Actions considered sequentially



$$K_C(m, \mathbf{y}) = \delta_{C(m)}(\mathbf{x})$$

$$\nu^{\delta_m}(m') = \sum_{\mathbf{y} \in \mathcal{Y}^n} \sum_{\mathbf{x} \in \mathcal{X}^n} \delta_{C(m)}(\mathbf{x}) Q_n(\mathbf{x}, \mathbf{y}) K_D(\mathbf{y}, m')$$

Net effect of channel: transform input message $M = m$ (distributed according to $\mu = \delta_m$) into random variable $M' \in \mathbb{M}$ of law ν^{δ_m} .

$$\begin{aligned} \nu^{\delta_m}(m') &= \mathbb{P}_m(M' = m') = \mathbb{P}(M' = m' | M = m) \\ &= \sum_{v \in \mathbb{M}} \mathbb{P}(M' = m' | M = v) \delta_m(v) = K_C Q_n K_D(m, m') \\ &= \sum_{\mathbf{x} \in \mathcal{X}^n} \sum_{\mathbf{y} \in \mathcal{Y}^n} K_C(m, \mathbf{x}) Q_n(\mathbf{x}, \mathbf{y}) K_D(\mathbf{y}, m') \\ &= \sum_{\mathbf{y} \in \mathcal{Y}^n} Q_n(C(m), \mathbf{y}) \delta_{\Delta(\mathbf{y}), m'} \end{aligned}$$

3-D : Explain steps.



Channel capacity

Transmission error

- Individual transmission error

$$\begin{aligned} e(m) &:= e^{(n)}(m) = \mathbb{P}_{\delta_m}(M' \neq m) = \sum_{m' \neq m} \sum_{\mathbf{y} \in \mathbb{Y}^n} Q_n(\mathbf{C}(m), \mathbf{y}) \delta_{\Delta(\mathbf{y}), m'} \\ &= \sum_{\mathbf{y} \in \mathbb{Y}^n} Q_n(\mathbf{C}(m), \mathbf{y}) \mathbb{1}_{\mathbb{M} \setminus \{m\}}(\Delta(\mathbf{y})). \end{aligned}$$

- Maximal transmission error

$$e_{\max} := e_{\max}^{(n)} = \max_{m \in \mathbb{M}} e^{(n)}(m).$$

- Mean transmission error

$$\bar{e} := \bar{e}^{(n)} = \sum_{m \in \mathbb{M}} \mu(m) e^{(n)}(m).$$

Channel capacity

Bloc codes

Definition

An $[n, k]$ -**bloc code** (with k and n integers ≥ 1) for a discrete memoryless channel $(\mathbb{X}, \mathbb{Y}, P)$ is the triple $(\mathbb{M}, \mathbf{C}, \Delta)$, where

- \mathbb{M} is the set of messages with $\text{card}\mathbb{M} = k$,
- $\mathbf{C} : \mathbb{M} \rightarrow \mathbb{X}^n$ is the bloc coding of size n ,
- $\Delta : \mathbb{Y}^n \rightarrow \mathbb{M}$ is the decoding.

Denote \mathcal{K} , more precisely $\mathcal{K}(n, k)$ (or simply $[n, k]$), such a code. The image $\mathbf{C}(\mathbb{M}) \subseteq \mathbb{X}^n$ is the **glossary of the code** \mathcal{K} .

Definition

Let \mathcal{K} an $[n, k]$ bloc code.

- **Transmission rate** R

$$R := R[\mathcal{K}] = \frac{\log_{|\mathbb{X}|} k}{n}.$$

- A transmission rate R is **attainable** if exists sequence $(\mathcal{K}_\ell)_{\ell \in \mathbb{N}}$ of $[n_\ell, k_\ell]$ -bloc codes, such that

$$\lim_{\ell \rightarrow \infty} \frac{\log_{|\mathbb{X}|} k_\ell}{n_\ell} \rightarrow R \text{ and } \lim_{\ell \rightarrow \infty} e_{\max}[\mathcal{K}_\ell] = 0.$$

Layout of Serbian keyboard
(at least as simulated on my computer)



$$M = \{a, z, e, r, \dots\}$$

$$\begin{array}{c}
 a \xrightarrow{M} a \\
 z \xrightarrow{M} z \\
 e \xrightarrow{M} e \\
 r \xrightarrow{M} r
 \end{array}$$

$$\begin{array}{c}
 M = X \rightarrow Y = M \\
 \uparrow
 \end{array}$$

Original messages

$$\{a, e, r, \dots\}$$

Layout of French keyboard



By rekeying the set M the channel becomes lossless

Error correction

$p = 0.1$



Residual R_3 code
error

if $p = 0.1$ is 0.03

$R_6 \rightarrow 10^{-15}$

Channel capacity

Fundamental theorem of transmission

Theorem (Shannon theorem for transmission)

Let $(\mathbb{X}, \mathbb{Y}, P)$ be a memoryless channel with capacity $\text{cap} := \text{cap}(P)$.

- For every $R < \text{cap}$, exists sequence $(\mathcal{K}_\ell)_{\ell \in \mathbb{N}}$ of $[n_\ell, k_\ell]$ -codes, with transmission rates $R_\ell := \frac{\log_{|\mathbb{X}|} k_\ell}{n_\ell} \rightarrow R$, such that $\lim_{\ell \rightarrow \infty} \bar{e}[\mathcal{K}_\ell] = 0$.
- Conversely, for every $R > \text{cap}$ and every sequence $(\mathcal{K}_\ell)_{\ell \in \mathbb{N}}$ of $[n_\ell, k_\ell]$ -codes with blocs of increasing size (i.e. $n_1 < n_2 < n_3 < \dots$) and transmission rates $R_\ell \geq R$, we have $\lim_{\ell \rightarrow \infty} \bar{e}[\mathcal{K}_\ell] = 1$.

Channel capacity

Fundamental theorem of transmission (cont'd)




Figure: For binary symmetric channel, with error rate $p = 0.1$, red curve is the Shannon boundary. Blue marks = transmission rates vs. residual error probability for the family of repetition ECC \mathcal{R}_n , with $n = 1, 3, 5, \dots, 61$.

Channel capacity

Exercise: capacity of the "sum" of two channels

Exercise

- Let $\mathcal{K}_i = (\mathbb{X}_i, \mathbb{Y}_i, P_i)$, $i = 1, 2$ be two channels.
 - Denote by $\mathbb{X} = \mathbb{X}_1 \boxplus \mathbb{X}_2$ (if \mathbb{X}_1 and \mathbb{X}_2 are distinct then $\mathbb{X}_1 \boxplus \mathbb{X}_2 = \mathbb{X}_1 \sqcup \mathbb{X}_2$; else, start by distinguishing artificially the elements of \mathbb{X}_1 and \mathbb{X}_2 before taking their union.)
 - Similarly for $\mathbb{Y} = \mathbb{Y}_1 \boxplus \mathbb{Y}_2$.
 - Transmission matrix of the "sum" is the bloc matrix $P = \begin{pmatrix} P_1 & 0 \\ 0 & P_2 \end{pmatrix}$.
 - X a \mathbb{X} -valued r.v. whose law described by $\pi \in \text{PV}_{\mathbb{X}}$ and Y a \mathbb{Y} -valued r.v. whose law determined by the channel.
- Compute $H(\pi)$. *Hint:* Let $p = \sum_{x \in \mathbb{X}_1} \pi(x)$ (hence $1 - p = \sum_{x \in \mathbb{X}_2} \pi(x)$.)
 - Compute $H(X|Y)$.
 - Consider r.v. X_1 and X_2 with values in \mathbb{X}_1 and \mathbb{X}_2 and laws ρ_1 and ρ_2 ; denote by Y_1 and Y_2 the restrictions to \mathbb{Y}_1 and \mathbb{Y}_2 of Y . Show that $H(X|Y) = pH(X_1|Y_1) + (1 - p)H(X_2|Y_2)$ and conclude that

$$C(p) := \sup_{\pi: \sum_{x \in \mathbb{X}_1} \pi(x) = p} I(X : Y) = H(p, 1 - p) + pC_1 + (1 - p)C_2.$$

- Show that $\arg \max_p C(p)$ is $p = \frac{2C_1}{2C_1 + 2C_2}$.
- Conclude that capacity of "sum" channel reads $2^C = 2^{C_1} + 2^{C_2}$.

